

“Product Passport” for the Easy 422 model

Ref: Easy422.01.07

Execution of this model:



- Split pot free standing fryer with two independent control panels
- Connection box of the heating elements made of coated die-cast aluminium, oil and water proof
- Standard control panels with simple knob and 3 control lights
- Selection of the frying temperature by steps of 5°C, from 150°C up to 190°C
- Integrated fat melting cycle
- Standby function (energy-saving)
- Precise temperature control of +/- 2°C by a thermocouple
- Electronic safety thermostat with an independent circuit
- Heating elements with special draining and cleaning position
- 24V components on the operating side
- Two oil receptacles (coarse and fine filters as optional extras)
- Two stainless steel baskets
- Level of protection IPX 3

Technical specifications:

- Economic power consumption: 2 x 7,5 kW – 4 Watt per cm²
- Tension: 2 x 3NAC400V 50/60Hz
- Fuse rating for 2 x 7,5 kW power: 2 x 3 x 16 A
- Supply line: 2 x 3L+N+PE
- Net weight without options: 58 kg
- Capacity of basket: 2 x 1,25 kg
- Recommended basket load: 2 x 0,9 kg
- Output per hour: 2 x 17 – 22 kg frozen French fires
- 2 x 20 – 25 kg pre-cooked French fries

Measurements:

- Width: 397,5 mm
- Depth: 650 mm
- Working height: 850 – 900 mm
- Total height: 943 – 993 mm
- Oil content: 2 x 7,5 – 9 lt.

Optional extras:

- Coarse filter with frame
 - Fine filter
- The fine filter can only be used in connection with the coarse filter.